



MICHI
PREMIUM MOTOR OIL



MICHI ULTRA 5W-30 GF-5

Premium synthetic motor oil

DESCRIPTION



Fully synthetic high-quality motor oil. Designed and manufactured to meet the requirements of leading automotive producers for enhanced environmental performance and fuel efficiency. Ideal for gasoline engines of Japanese, Korean, and Chinese manufacturers (Toyota, Nissan, Honda, Mitsubishi, Kia, Hyundai, Chery, Haval, Geely, and others).

RECOMMENDED FOR



- API SN
- ILSAC GF-5

APPLICATION



Modern gasoline engines in passenger cars where oils meeting API SN and ILSAC GF-5 standards are recommended. Perfectly suited for a wide range of Japanese, Chinese and Korean engines. Provides an excellent balance between fuel economy and extended engine life.

FEATURES & BENEFITS



- Optimal balance between fuel efficiency and oil film thickness
- A special additive package significantly reduces the formation of deposits and ensures engine cleanliness
- The oil's strong detergency and neutralizing capacity help protect it against oxidation
- Low viscosity at negative temperatures ensures easy starting in extremely cold climates and helps prevent wear during engine start
- Superior wear protection in all operating conditions

TYPICAL CHARACTERISTICS



PROPERTIES	METHOD	VALUE
Density at 15°C, kg/m ³	ASTM D4052	847
Kinematic Viscosity at 100°C, cSt	ASTM D445	10.8
Viscosity Index	ASTM D2270	162
CCS Viscosity -30.°C, cP	ASTM D5293	5880
Pour Point, °C	ASTM D2896	-42
TBN, mg KOH/g	ASTM D 5800	8.8
Evaporation Loss NOACK, %	ASTM D92	9.9
Flash Point, °C	ASTM D97	230
Sulphated Ash, %	ASTM D874	0.84

The properties listed are typical for the product currently in production. Due to ongoing research and development, the information provided in this document is subject to change.